



Challenger[®] Series

THERMAL TRANSFER PRINTERS



The *Challenger*[®] Series symbolizes *Performance, Value and Reliability*. These printers are equipped with a 32 bit Motorola RISC processor that ensures a fast first label output and serialized data printing. The entire series features a robust all metal construction designed to withstand adverse operating conditions making them ideal for heavy-duty industrial applications.

Challenger[®] series printers print high quality bar codes, bitmapped images, graphics, scalable resident fonts & Windows True Type fonts at 203 dpi / 300 dpi. These printers are suitable for applications such as document tracking, inventory management, product labeling, dispatch labeling, manufacturing, labeling medical records & ticket printing.

All the *Challenger*[®] series printers are backed by a warranty of three-years or 3 million linear inches on the printer, which covers all parts except print head and a print head warranty of six months or 1 million linear inches against manufacturing defects.

Challenger[®] series printers can emulate the Datamax printer language and are a drop in replacement for the Allegro-2 and E-4203 Datamax printers.

Challenger[®] Series Features :

- ❖ Three years or 3 million linear inches limited warranty (whichever is early) on the printers except the print head.
- ❖ Six months or 1 million linear inches on the print head against manufacturing defects.
- ❖ Standard Rugged metal cover to ensure reliable operation in harsh environments.
- ❖ 32-bit Motorola 68 K Processor.
- ❖ Latest Japanese print head from Kyocera, Japan
- ❖ Industrial grade metal print mechanism ensures long lasting print registration & print quality.
- ❖ Ability to print any Windows True Type font easily with help of the Font Utility provided.

Challenger[®] Series 4203E, 4203, 4205 and 4303 Product Specifications

Challenger[®]
Series

	4203E	4203/4205	4303
PRINT SPEED	3 IPS	3 IPS / 5 IPS	3 IPS
RESOLUTION	203 dpi	203 dpi	300 dpi
DIMENSIONS	(H) 8.34" x (W) 9.25" x (D) 9.44" 212 mm x 235 mm x 240 mm	(H) 8.34" x (W) 9.25" x (D) 13" 212 mm x 235 mm x 330 mm	(H) 8.34" x (W) 9.25" x (D) 13" 212 mm x 235 mm x 330 mm

PRINTER TYPE	Direct Thermal or Thermal Transfer
MAX PRINT WIDTH	4.1"(104 mm)
MEDIA WIDTH	1" - 4.65" (25 mm - 118 mm)
PRINT LENGTH	0.5" - 9" (12.7mm - 228.6mm)
BAR CODE MODULUS	5 mil to 150 mil (203 dpi) 3.3 mil to 150 mil (300 dpi) "X" dimension in picket fence or ladder orientations
MEDIA WINDOW	Clear side-door panel to easily monitor media supply levels
MEDIA TYPE	Roll-fed or fan-fold materials, die-cut or continuous labels; perforated or continuous tag/ticket stock
MEDIA THICKNESS	.0025" - .0100" (.0635mm - .254mm)
MEDIA SENSING	"See through" for liner backed die cut Labels & tags; left bias reflective sensor for media with black stripe sensing
SUPPLY ROLL	8" (203mm) maximum diameter on 1.5" - 3" (38mm- 76mm) core. Fan-fold stock accepted from rear of printer
LABEL BACKFEED	For use with tear bar
RIBBONS	Industry standard ribbon widths; 1" (25mm) ribbon core, 1182' (360M) in length, Coated inside
CABINET	Powder coated metal cabinet
BAR CODES	Code 3 of 9, UPC-A, UPC-E, Interleaved 2 of 5, Code 128, EAN-8, EAN-13, Codabar, Plessey, UPC 2 and 5 digit addendums, Code 93, UCC/EAN Code 128, PDF417, Datamatrix
RESIDENT FONTS	Nine alphanumeric fonts from 1.0 mm (0.039") to 12 mm (0.64"), including OCR-A, OCR-B.
DOWNLOADABLE FONT TYPES	Any windows font can be downloaded in the FLASH for printing. Through the windows utility provided, a windows True Type Fonts can be downloaded in the printer FLASH memory for printing.
CHARACTER SET	Modified IBM® Code Page 850 includes characters for English.
FONT EXPANSION/ROTATION	All fonts expandable vertically and horizontally up to 9x, fonts and graphics can be printed in four directions: 0°, 90°, 180° and 270°
GRAPHICS SUPPORT	PCX, .BMP and .IMG files
REVERSE FIELDS/MIRROR IMAGE	Any font or graphic field can be printed as a normal or reverse image
MEMORY	1MB Downloadable Flash Program Memory
INTERFACES	Centronics® Parallel port IEEE 1284 compliant and RS232 at 2,400 to 9600 BPS; optional Ethernet, USB
POWER SOURCE	90 - 264 VAC @ 47 - 63 Hz
OPERATING TEMPERATURE	4°C to 40°C (40°F to 110°F)

Option

CUTTER WITH TRAY	Maximum Thickness 0.254 mm (0.1")
LABEL PRESENT SENSOR	Used for on-demand label dispensing and peel & present applications
INTERNAL REWIND	50 mm (2") OD Capacity, label backing rewound in peel & present mode
EXTERNAL REWIND	203 mm (8") maximum OD capacity

This data sheet is for informational purposes only. ID Technologies MAKES NO WARRANTIES, EXPRESSED OR IMPLIED IN THIS SUMMARY. Specifications are subject to change without notice. All trademarks are the property of their respective owners.

Distributed By