

# HPRT LPQ58

## 2" Thermal Label Printer Specification



**Printing**

Printing Method	Direct Thermal
Resolution	203 dpi (8 dots/mm)
Printing Speed	2 ips ~ 3 ips
Printing Width	Max. 56 mm
Printing Length	15 mm ~ 400mm

**Memory**

RAM	2 MB
Flash	2 MB

**Sensors**

Gap Sensor	Transmissive (Fixed, Center)
Black Mark Sensor	Reflective (Adjustable, Full-Range)
Other	Out of paper detection, Notch detection, TPH temperature detection

**Media**

Types	Fan-fed or Roll-fed, Die-cut or Continuous Label, Receipt
Width	1"(25.4 mm) ~ 2.28"(58 mm)
Thickness	0.003"(60 $\mu$ m) ~ 0.007"(180 $\mu$ m)
Label Roll Diameter	90 mm
Core Diameter	0.5"(12.7 mm), 1"(25.4 mm), 1.5"(38.1 mm)

**Programming Language**

TSPL, ESC/POS

**Software**

Label Designer	Bartender Ultralite by Seagull
Driver	Windows XP/Vista/7/8/8.1/10

**Fonts**

Bitmap Fonts	6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° rotatable and 10 times expandable in horizontal and vertical directions
--------------	--

---

<b>Code Pages</b>		PC437, 720, 737, 755, 775, 850, 852, 855, 856, 857, 858, 860, 862, 863, 864, 865, 866; Windows1250, 1251, 1252, 1253, 1254, 1255, 1256, 1257, 1258; ISO8859-1, 2, 3, 4, 5, 6,
<b>Barcode</b>	Barcode	CODE39, CODE93, EAN-8, EAN-13 (with EAN-2 or EAN-5 add-on), UPC-A, UPC-E
	2D Code	QR Code
<b>Interfaces</b>	Standard	USB, Serial Port, Cashbox
	Option	N/A
<b>Control Panel</b>		Power button, Feed button
<b>Power Adapter</b>	Power Input	AC 100 ~ 240V, 50/60Hz, 1.5A
	Power Output	DC 12V, 2A
<b>Environment</b>	Operation	41 °F ~ 104 °F (5 °C ~ 40 °C), 30% ~ 85%, no-condensing
	Storage	-4 °F ~ 122 °F (-20 °C ~ 50 °C), 10% ~ 50%, no-condensing
<b>Physical Characteristics</b>	Dimension	186(L)×128(H)×133(W) mm
	Weight	0.805 kg
<b>Options and Accessories</b>		External label roll holder
<b>Agency Approvals</b>		CCC, FCC, CE

---