

HD 755 | REPORT PRINTER

The high speed heavy duty printer



Top printing speed -
435 cps



Print head life - 200
million characters



High reliability - 10,000
POH MTBF



Dual interface - Parallel &
USB with auto switching



Higher copy capability -
1+4 copies

Specifications

Print Method : Serial impact dot matrix
 Print Direction : Bi-directional logic seeking
 Print Head Type : 9 wire
 Print Width : 136 column
 Print Head Life : 200 million characters*

Print Speed

Super Speed Draft : 435
 @ 12 cpi
 High Speed Draft : 387
 @ 10 cpi
 Draft @ 10 cpi : 290
 Near Letter : 73
 Quality @ 10 cpi

Resident Printer Fonts

Draft : Gothic
 Near Letter Quality : Courier, Gothic
 Letter Quality Scalable Fonts : Courier, Gothic (22 to 216 points in 1 pt increments)
 Resident Barcode Fonts : Code 39, UPC A, UPC E, EAN8, EAN13, interleaved 2 of 5, Code 128, PostNet

Paper Handling

Paper Path - Standard : Top, rear and bottom
 Continuous Feed - Tractor : Rear push

Optional

Continuous Tractor Feed : Bottom push & top pull
 Auto Sheet Feeder : Single bin - 50 pages

Paper Size

Continuous Form Width : 3.0" - 16"
 Cut Sheets Width : 7.2" - 14.3"
 Paper Thickness : Tractor feed 0.36 mm for rear & 0.44 mm for bottom friction feed 0.3mm
 Copy Capability* : 1+4 with carbon

Consumables - Ribbon

Fabric - Ink Type : Super high density - seamless
 Fabric Life** : 3 million characters
 Input Buffer (Kilo Bytes) : 88 KB

Reliability

MTBF (Power on Hours) : 10,000 POH**
 Acoustics - Noise Level : 57 dB (A) in normal mode
 52 dB (A) in quiet mode
 Emulation : Epson FX, IBM Proprinter, OKI Microline

Interface

Standard : Centronics Parallel & USB (Auto interface switching)
 Optional : RS-232C Serial

Software Specifications

Drivers : Windows 95, 98, 98SE, 2000, Me, XP, NT 4.0, Linux Redhat

Electrical Specifications

Operating Voltage : 198 - 264V AC
 Mains Frequency : 50 - 60 Hz
 Power (Standby) : 10 W

Environmental - Operating Conditions

Temperature : +5° C to +45° C
 Relative Humidity : 20% to 80%

Physical Dimensions

Size (W x D x H) mm : 552 x 116 x 345
 Weight : 8.5 kg
 Warranty : 1 year

Best suited for printing

Invoices | Ledgers | Accounts & Statements | Barcode printing

1 kg = 2.2 lbs; 1 inch = 2.54 cms

*Max. possible copy capability

**@ Draft 10 cpi

##@ 33% print density and 25% duty cycle

Excluding print head @ 33% print density and 25% duty cycle

in lieu of USB

CUSTOMER SEGMENTS



Transport Companies



Corporate Offices



Manufacturing Companies

ORDERING INFORMATION

3006030002 HD 755

OPTIONAL CONSUMABLES

2027070007 TVS-E RIBBON CASSETTE HD7XX/9XX

2023020003 TVS-E PRINT HEAD HD 755

DEALER STAMP

TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor,

Industrial Estate, Guindy, Chennai - 600 032.

Call: 1800 200 5123 / 3030 9797 / 3030 7171 (prefix city STD code)

Visit: www.tvse.in